

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number
WO 2005/068271 A1

(51) International Patent Classification⁷: **B60T 8/00**

(21) International Application Number:
PCT/EP2004/000113

(22) International Filing Date: 9 January 2004 (09.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **NIRA DYNAMICS AB** [SE/SE]; Teknikringen 1F, S-583 30 Linköping (SE).

(71) Applicant (for US only): **DREVÖ, Markus** [SE/SE]; Abylundsgatan 54, S-582 36 Linköping (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LINDSKOG, Peter**

[SE/SE]; Bygdegatan 420, S-583 31 Linköping (SE).
SJÖSTRAND, Niclas [SE/SE]; Trumslagaregatan 38, S-582 16 Linköping (SE).


(74) Agents: **JACOBY, Georg** et al.; Samson & Partner, Widenmayerstrasse 5, 80538 München (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: ESTIMATION OF THE ROAD CONDITION UNDER A VEHICLE



(57) Abstract: A system for estimating the ground condition under a driving vehicle, comprising: a wheel speed sensor (4) for sensing a wheel speed signal ($t(n)$, $\omega(n)$) which is indicative of the wheel speed of a vehicle's wheel driving over the ground (2,3) and a first analyser unit (8) coupled to said wheel speed sensor (4). The first analyser unit comprises a sensor imperfection estimation section (9) which is designed to estimate a sensor imperfection signal, formula (I), from the wheel speed signal ($t(n)$) which is indicative of the sensor imperfection of the wheel speed sensor (4); a signal correction section (10) which is designed to determine an imperfection-corrected sensor signal ($\epsilon(n)$) from the wheel speed signal ($t(n)$) and the sensor imperfection signal, formula (I); and a ground condition estimation section (11) which is designed to estimate a first estimation value ($r(n)$, $\alpha(n)$) indicative of the ground condition from the imperfection-corrected sensor signal ($\epsilon(n)$).

$$(\hat{\delta}_i)_{(1)}$$



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*